

## Feature

- Absorbs all counterforce produced by the assembly tool, reducing operator fatigue.
- Allows operator to effortlessly position tool at any location and counteracts tool's weight.
- Easy to assemble.



EAA-AUXA-500  
EAA-AUXB  
EAA-AUX1A  
EAA-AUX1A-B

## 90° adaptor

Allows the operator to adjust the angle of the tool in accordance with the workpiece.



With extra 90° adaptor

EAA-AUX-500  
EAA-AUX  
EAA-AUX7  
EAA-AUX1  
EAA-AUX1-B



Fasten the workpiece in vertical.



## Specifications :

Model No.	EAA-AUXA-500 EAA-AUX-500	EAA-AUXB EAA-AUX	EAA-AUX7	EAA-AUX1A EAA-AUX1	EAA-AUX1A-B EAA-AUX1-B
Description	Suspension Arm	Suspension Arm	Suspension Arm	Suspension Arm	Suspension Arm
Reach (mm)	50 ~ 830	50 ~ 830	50 ~ 830	50 ~ 830	50 ~ 830
Capacity (kgs)	Max 4	Max 4	Max 4	Max 3	Max 3
Gas Spring (kgs)	35	25	25	20	20
Applicable Model	EA-BAK9250L(P)H EN-BAN9350~ EN-BAN9500	EA-BAK960 ~ EA-BAK9250 <i>EA-BAK9250L(P)H is not included.</i>	EA-BK760~ EA-BK7120	EA-712 ~ EA-745 ED-617 ~ ED-645	EA-BN630 ~ EA-BN650 EA-BD630 ~ EA-BD650